


U/UTP 4Pairs cable-category5E-PVC Sheath

P/N: HK-1191-C5E-001-03

Content of the Data Sheet																																																																																																												
	HIKVISION E484059-Z CM (UL) 4PR 24AWG 75℃ U/UTP CAT5E VERIFIED TO ANSI/TIA-568-C.2 PVC ****m mm/dd/yyyy																																																																																																											
Customer Reference					White-Blue /Blue White-Orange/Orange Sheath Rip-cord White- Brown /Brown White- Green /Green 																																																																																																							
Category	U/UTP CAT5E-4P- PVC-CM																																																																																																											
Test Standard	ISO/IEC11801、TIA-568-C.2 YD/T1019																																																																																																											
Conductor	Material	Solid-Bare Copper																																																																																																										
	Nom.O.D.(mm)	0.500	up	+0.005																																																																																																								
			down	-0.005																																																																																																								
Insulation	Material	HDPE																																																																																																										
	Diameter	0.88±0.03mm																																																																																																										
Sheath	Thickness	0.50±0.05 mm			Technical Performance(100m): <table><thead><tr><th>Frequency (MHz)</th><th>RL ≥dB</th><th>ATT ≤dB</th><th>NEXT ≥dB</th><th>Phase DELAY ≤ns</th></tr></thead><tbody><tr><td>1</td><td>20.0</td><td>2.0</td><td>65.3</td><td>570.00</td></tr><tr><td>4.0</td><td>23.0</td><td>4.1</td><td>56.3</td><td>552.00</td></tr><tr><td>8.0</td><td>24.5</td><td>5.8</td><td>51.8</td><td>546.73</td></tr><tr><td>10.0</td><td>25.0</td><td>6.5</td><td>50.3</td><td>545.38</td></tr><tr><td>16.0</td><td>25.0</td><td>8.2</td><td>47.2</td><td>543.00</td></tr><tr><td>20.0</td><td>25.0</td><td>9.3</td><td>45.8</td><td>542.05</td></tr><tr><td>25.0</td><td>24.3</td><td>10.4</td><td>44.3</td><td>541.20</td></tr><tr><td>31.25</td><td>23.6</td><td>11.7</td><td>42.9</td><td>540.44</td></tr><tr><td>62.5</td><td>21.5</td><td>17.0</td><td>38.4</td><td>538.55</td></tr><tr><td>100</td><td>20.1</td><td>22.0</td><td>35.3</td><td>537.60</td></tr></tbody></table> <table><thead><tr><th>Frequency (MHz)</th><th>PSNEXT ≥dB</th><th>ELFEXT ≥dB</th><th>PSELFEXT ≥dB</th></tr></thead><tbody><tr><td>1</td><td>62.3</td><td>63.8</td><td>60.8</td></tr><tr><td>4</td><td>53.3</td><td>51.8</td><td>48.8</td></tr><tr><td>8</td><td>48.8</td><td>45.7</td><td>42.7</td></tr><tr><td>10</td><td>47.3</td><td>43.8</td><td>40.8</td></tr><tr><td>16</td><td>44.4</td><td>39.7</td><td>36.7</td></tr><tr><td>20</td><td>42.8</td><td>37.8</td><td>34.8</td></tr><tr><td>25</td><td>41.3</td><td>35.8</td><td>32.8</td></tr><tr><td>31.25</td><td>39.9</td><td>33.9</td><td>30.9</td></tr><tr><td>62.5</td><td>35.4</td><td>27.9</td><td>24.9</td></tr><tr><td>100</td><td>32.3</td><td>23.8</td><td>20.8</td></tr></tbody></table>					Frequency (MHz)	RL ≥dB	ATT ≤dB	NEXT ≥dB	Phase DELAY ≤ns	1	20.0	2.0	65.3	570.00	4.0	23.0	4.1	56.3	552.00	8.0	24.5	5.8	51.8	546.73	10.0	25.0	6.5	50.3	545.38	16.0	25.0	8.2	47.2	543.00	20.0	25.0	9.3	45.8	542.05	25.0	24.3	10.4	44.3	541.20	31.25	23.6	11.7	42.9	540.44	62.5	21.5	17.0	38.4	538.55	100	20.1	22.0	35.3	537.60	Frequency (MHz)	PSNEXT ≥dB	ELFEXT ≥dB	PSELFEXT ≥dB	1	62.3	63.8	60.8	4	53.3	51.8	48.8	8	48.8	45.7	42.7	10	47.3	43.8	40.8	16	44.4	39.7	36.7	20	42.8	37.8	34.8	25	41.3	35.8	32.8	31.25	39.9	33.9	30.9	62.5	35.4	27.9	24.9	100	32.3	23.8	20.8
	Frequency (MHz)	RL ≥dB	ATT ≤dB	NEXT ≥dB						Phase DELAY ≤ns																																																																																																		
	1	20.0	2.0	65.3						570.00																																																																																																		
	4.0	23.0	4.1	56.3						552.00																																																																																																		
	8.0	24.5	5.8	51.8						546.73																																																																																																		
10.0	25.0	6.5	50.3	545.38																																																																																																								
16.0	25.0	8.2	47.2	543.00																																																																																																								
20.0	25.0	9.3	45.8	542.05																																																																																																								
25.0	24.3	10.4	44.3	541.20																																																																																																								
31.25	23.6	11.7	42.9	540.44																																																																																																								
62.5	21.5	17.0	38.4	538.55																																																																																																								
100	20.1	22.0	35.3	537.60																																																																																																								
Frequency (MHz)	PSNEXT ≥dB	ELFEXT ≥dB	PSELFEXT ≥dB																																																																																																									
1	62.3	63.8	60.8																																																																																																									
4	53.3	51.8	48.8																																																																																																									
8	48.8	45.7	42.7																																																																																																									
10	47.3	43.8	40.8																																																																																																									
16	44.4	39.7	36.7																																																																																																									
20	42.8	37.8	34.8																																																																																																									
25	41.3	35.8	32.8																																																																																																									
31.25	39.9	33.9	30.9																																																																																																									
62.5	35.4	27.9	24.9																																																																																																									
100	32.3	23.8	20.8																																																																																																									
	External O.D.	5.0±0.4 mm																																																																																																										
	Surface	Clean,Frap,Satiation																																																																																																										
	Material	PVC(complies RoHS),CM																																																																																																										
	Color	Multiple																																																																																																										
Surface Printing	Letter height	3.0±0.3mm																																																																																																										
	Color	Black																																																																																																										
	Print error & Space	≤±0.5%, 1m																																																																																																										
Core Color	1 White- Blue /Blue		2 White-Orange /Orange																																																																																																									
	3 White- Green /Green		4 White- Brown /Brown																																																																																																									
Packing	Wooden Tray & Carton																																																																																																											
Carton dimension	Per request																																																																																																											
Packing length	(305±1.5)m																																																																																																											
Rip-cord	Yes	Drain wire		No																																																																																																								
Sheath Physical Properties	Before Aging Tensile Strength (Mpa)		≥13.5																																																																																																									
	Elongation(%)		≥150																																																																																																									
	Aging Period(℃×hrs)		100℃×24h×10d																																																																																																									
	After Aging Tensile Strength(Mpa)		≥12.5																																																																																																									
	Elongation(%)		≥125																																																																																																									
	Cold bend(-20±2℃×4h) 8×Cable O.D., No visible cracks																																																																																																											
Electrical Characteristics (20℃)	1.0-100.0MHz Impedance(Ω)		100±15																																																																																																									
	1.0-100.0MHz Delay Shew (ns/100m)		≤45																																																																																																									
	DC ResistanceΩ/100m) max		9.5																																																																																																									
	DC Conductor Resistance Unbalance(%) max		5.0																																																																																																									
Ambient temperature: -20℃ - 75℃																																																																																																												