



tesamoll® UNIVERSAL door-to-floor foam

BNR 5422

Product Features

- Stops draughts, dust, cold, warmth, noise and insects
- For even floors
- Quick and easy to apply
- Long-lasting

tesamoll® UNIVERSAL Door-to-Floor Foam is a cost-effective alternative to brush-type door draught stoppers. It is able to seal door-to-floor gaps up to 20 mm.

Product Construction

- | | | | |
|--------------------|------------------|----------------|-------|
| • Type of adhesive | synthetic rubber | • Gap coverage | 20 mm |
| • Backing material | PP film-PU foam | | |

Product Properties/Performance Values

- | | | | |
|------------------------|---------|----------------|-----|
| • Durability | 2 years | • Solvent free | yes |
| • Residue free removal | no | | |

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user’s method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=NaN>